2016/10/27

Raynox Conversion Lens Compatible Table for Canon XC10 / XC15 Ultra High Definition Camcorders

Model	Magnification	Required Adapter	Video Mode 16:9	Distance to the Object/ Minimum shooting distance	Effective Zooming without vignetting
HDP-7880ES	0.79x	RA6258(Included)		1cm	1x-5x
HDP-5072EX	0.5x	RA7258		1cm	1x-4x
DCR-FE181PRO	0.24x	RA6258(Included)		1cm	1x-3x*1
DCR-CF187PRO	0.21x	RA6258(Included)		1cm	Use at the max.wideangle position*2
DCR-1542PRO	1.54x	RA5258A		about 2m	4x-10x
DCR-2025PRO	2.2x	RA6258(Included)		about 5m	Use at the max.telephoto position
HDP-9000EX	1.8x	RA7258		about 2m	8x-10x
DCR-5320PRO	2-diopter	RA7258	64.1mm*	Distance to the object 486mm (Focusing set at infinity)	1x-10x
	3-diopter		42.7mm*	Distance to the object 311mm (Focusing set at infinity)	2x-10x
	5-diopter		25.6mm*	Distance to the object 170mm (Focusing set at infinity)	2x-10x
DCR-150	4.8-diopter	UAC2000(Included)	26mm*	Distance to the object 210mm (Focusing set at infinity)	3x-10x
DCR-250	8-diopter	UAC2000(Included)	16mm*	Distance to the object 109mm (Focusing set at infinity)	3x-10x
MSN-202	25-diopter	UAC3500(Included)	5mm*	Distance to the object 32mm (Focusing set at infinity)	4x-10x
MSN-505	32-diopter	UAC3500(Included)	4mm*	Distance to the object 18.5mm (Focusing set at infinity)	8x-10x

Imaging Sensor : l.0-inch CMOS Sensor, f8.9to 89 mm, (35mm equivalent) : Movie Mode:27.3 to 273 mm (16:9),Optical Zoom : 10x ,Filter Diameter : 58mm

・Remove camera's lens hood before mounting the conversion lens.

* 1 DCR-FE181PRO can be used as fisheye. It may create vignetting at f=8.9mm(max wideangle positon).

Vignetting may disapper at f=11.9mm by zooming and its magnification becomes about 0.32x horizontal.

* 2 DCR-CF187PRO can be used as circular fisheye.

* The size of width captured on full LCD screen.